
SZCJ

Shenzhen Changji Semiconductor Co., LTD.

# SOT-353 Plastic-Encapsulate Diodes

## UMN1N SWITCHING DIODE





**FEATURES**

- Multiple Diodes in One Small Surface Mount Package
- Diode Characteristics are Matched in the Package

**APPLICATIONS**

- High Speed Switching

**MARKING: N1**




Solid dot = Green molding compound device.

**MAXIMUM RATINGS ( $T_a$=25℃ unless otherwise noted )**


| Symbol | Parameter | Value | Unit |
|---|---|---|---|
| $V_R$ | Continuous Reverse Voltage | 80 | V |
| $I_O$ | Continuous Forward Current | 25 | mA |
| $I_{FM}$ | Peak Forward Current | 80 | mA |
| $I_{FSM}$ | Non-repetitive Peak Forward Surge Current@t=8.3ms | 0.25 | A |
| $P_D$ | Power Dissipation | 150 | mW |
| $R_{\theta JA}$ | Thermal Resistance From Junction To Ambient | 833 | ℃/W |
| $T_J$ ,$T_{stg}$ | Operation Junction and Storage Temperature Range | -55~+150 | ℃ |

**ELECTRICAL CHARACTERISTICS($T_a$=25℃ unless otherwise specified)**


| Parameter | Symbol | Test conditions | Min | Typ | Max | Unit |
|---|---|---|---|---|---|---|
| **Reverse voltage** | $V_{(BR)}$ | $I_R$=100μA | 80 | | | V |
| **Reverse current** | $I_R$ | $V_R$=70V | | | 0.1 | μA |
| **Forward voltage** | $V_F$ | $I_F$=5mA | | | 0.9 | V |
| **Total capacitance** | $C_{tot}$ | $V_R$=6V,f=1MHz | | | 3.5 | pF |
| **Reverse recovery time** | $t_{rr}$ | $I_F$= $I_R$=5mA, $V_R$=6V, $R_L$=50Ω | | | 4 | ns |

## Typical Characteristics


**Forward Characteristics**





**Reverse Characteristics**





**Capacitance Characteristics**






**Power Derating Curve**



## SOT-353 Package Outline Dimensions





| Symbol | Dimensions In Millimeters | | Dimensions In Inches | |
|---|---|---|---|---|
| | Min | Max | Min | Max |
| A | 0.900 | 1.100 | 0.035 | 0.043 |
| A1 | 0.000 | 0.100 | 0.000 | 0.004 |
| A2 | 0.900 | 1.000 | 0.035 | 0.039 |
| b | 0.150 | 0.350 | 0.006 | 0.014 |
| c | 0.100 | 0.150 | 0.004 | 0.006 |
| D | 2.000 | 2.200 | 0.079 | 0.087 |
| E | 1.150 | 1.350 | 0.045 | 0.053 |
| E1 | 2.150 | 2.400 | 0.085 | 0.094 |
| e | 0.650 TYP | | 0.026 TYP | |
| e1 | 1.200 | 1.400 | 0.047 | 0.055 |
| L | 0.525 REF | | 0.021 REF | |
| L1 | 0.260 | 0.460 | 0.010 | 0.018 |
| θ | 0° | 8° | 0° | 8° |

## SOT-353 Suggested Pad Layout





Note:
1.Controlling dimension:in millimeters.
2.General tolerance:±0.05mm.
3.The pad layout is for reference purposes only.

NOTICE

SZCJ reserves the right to make modifications,enhan nts,improvements,corrections or other es without further notice to any product herein. SZCJ does not assume any liability arising out of the application or use of any product described h

# SOT-353 Tape and Reel

## SOT-353 Embossed Carrier Tape





Packaging Description:


SOT-353 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 17.8cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

| Dimensions are in millimeter | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
| Pkg type | A | B | C | d | E | F | P0 | P | P1 | W |
| SOT-353 | 2.25 | 2.55 | 1.20 | Ø1.50 | 1.75 | 3.50 | 4.00 | 4.00 | 2.00 | 8.00 |

## SOT-353 Tape Leader and Trailer




## SOT-353 Reel




| Dimensions are in millimeter | | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| Reel Option | D | D1 | D2 | G | H | I | W1 | W2 |
| 7"Dia | Ø178.00 | 54.40 | 13.00 | R78.00 | R25.60 | R6.50 | 9.50 | 12.30 |

| REEL | Reel Size | Box | Box Size(mm) | Carton | Carton Size(mm) | G.W.(kg) |
|---|---|---|---|---|---|---|
| 3000 pcs | 7 inch | 45,000 pcs | 203×203×195 | 180,000 pcs | 438×438×220 | |