
SZCJ

Shenzhen Changji Semiconductor Co., LTD.

SOT-363 Plastic-Encapsulate Diodes

MMBD4448HAQW/HADW/HCDW/HSDW/HTW/HCQW









SOT-363



Switching Diode

FEATURES

- Fast Switching Speed
- Ultra-Small Surface Mount Package
- For General Purpose Switching Applications
- High Conductance Power Dissipation

MMBD4448HAQW	MMBD4448HADW	MMBD4448HCDW	MMBD4448HSDW	MMBD4448HTW	MMBD4448HCQW
					
MARKING:KA5	MARKING:KA6	MARKING:KA7	MARKING: KAB	MARKING:KAA	MARKING: KA4
					

Solid dot = Pin1 indicate.
Solid dot = Green molding compound device.

Maximum Ratings and Electrical Characteristics, Single Diode @T_a=25℃

Parameter	Symbol	Limit	Unit
Non-Repetitive Peak Reverse Voltage	V_{RM}	100	V
Peak Repetitive Peak Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_R	80	V
RMS Reverse Voltage	$V_{R(RMS)}$	57	V
Forward Continuous Current	I_{FM}	500	mA
Average Rectified Output Current	I_O	250	mA
Non-Repetitive Peak Forward Surge Current @t=8.3ms	I_{FSM}	2.0	A
Power Dissipation	Pd	200	mW
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$	625	℃/W
Operation Junction and Storage Temperature Range	T_J, T_{STG}	-55 ~+150	℃


ELECTRICAL CHARACTERISTICS

Electrical Ratings @Ta=25℃


Parameter	Symbol	Min	Typ	Max	Unit	Conditions
Reverse Breakdown Voltage	$V_{(BR)}$	80			V	I_R=100μA
Forward Voltage	V_{F1}	0.62		0.72	V	I_F=5mA
	V_{F2}			0.855	V	I_F=10mA
	V_{F3}			1.0	V	I_F=100mA
	V_{F4}			1.25	V	I_F=150mA
Reverse Current	I_{R1}			100	nA	V_R=70V
	I_{R2}			25	nA	V_R=20V
Capacitance Between Terminals	C_T			3.5	pF	V_R=0V,f=1MHz
Reverse Recovery Time	t_{rr}			4	ns	I_F=I_R=10mA Irr=0.1XI_R,R_L=100Ω

Typical Characteristics


Forward Characteristics




Reverse Characteristics




Capacitance Characteristics



Power Derating Curve




SOT-363 Package Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.100	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.000	0.035	0.039
b	0.150	0.350	0.006	0.014
c	0.100	0.150	0.004	0.006
D	2.000	2.200	0.079	0.087
E	1.150	1.350	0.045	0.053
E1	2.150	2.400	0.085	0.094
e	0.650 TYP		0.026 TYP	
e1	1.200	1.400	0.047	0.055
L	0.525 REF		0.021 REF	
L1	0.260	0.460	0.010	0.018
θ	0°	8°	0°	8°

SOT-363 Suggested Pad Layout




Note:
1.Controlling dimension:in millimeters.
2.General tolerance:±0.05mm.
3.The pad layout is for reference purposes only.

NOTICE

SZCJ reserves the right to make modifications,enhan nts,improvements,corrections or other es without further notice to any product herein. SZCJ does not assume any liability arising out of the application or use of any product described h

SOT-363 Tape and Reel

SOT-363 Embossed Carrier Tape




Packaging Description:


SOT-363 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 3,000 units per 7" or 17.8cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
SOT-363	2.25	2.55	1.20	Ø1.50	1.75	3.50	4.00	4.00	2.00	8.00

SOT-363 Tape Leader and Trailer



SOT-363 Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7"Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
3000 pcs	7 inch	45,000 pcs	203×203×195	180,000 pcs	438×438×220	