SZCJ

Shenzhen Changji Semiconductor Co., LTD.

KBL Plastic-Encapsulate Bridge Rectifier

KBL6005 THRU KBL610

General Purpose Bridge Rectifier

Features

- I_O 6A
- VRRM 50V-1000V
- High surge current capability
- Glass passivated chip


Applications

- General purpose 1 phase Bridge rectifier applications

Marking

- KBL6XX

XX：From 005 To 10



Limiting Values (Absolute Maximum Rating)

Item	Symbol	Unit	Conditions	KBL6						
				005	01	02	04	06	08	10
Repetitive Peak Reverse Voltage	V_{RRM}	V		50	100	200	400	600	800	1000
Average Rectified Output Current	I_O	A	60Hz sine wave, R-load T_a =40℃	6						
Surge(Non-repetitive)Forward Current	I_{FSM}	A	60H_Z half-sine wave, 1 cycle, T_j=25℃	150						
Current Squared Time	I^2t	A^2S	1ms≤t<8.3ms Tj=25℃， Rating of per diode	93.375						
Storage Temperature	T_{stg}	℃		-55 ~+150						
Junction Temperature	T_j	℃		-55 ~+150						

Electrical Characteristics（T_a=25℃ Unless otherwise specified）

Item	Symbol	Unit	Test Condition	Max
Peak Forward Voltage	V_{FM}	V	I_{FM}=6.0A, Pulse measurement, Rating of per diode	1.1
Peak Reverse Current	I_{RRM}	μA	V_{RM}=V_{RRM} , Pulse measurement, Rating of per diode	10
Thermal Resistance	$R_{\theta J-A}$	℃/W	Between junction and ambient	9
	$R_{\theta J-C}$		Between junction and case	2.4

Typical Characteristics

FIG.1-MAXIMUM NON-REPETITIVE SUNRGE CURRENT




FIG.2-FORWARD CURRENT DERATING CURVE




FIG.3-TYPICAL FORWARD CHARACTERISTICS






FIG.4-TYPICAL REVERSE CHARACTERISTICS



KBL Package Outline Dimensions



Dimensions in inches and (milimeters)

NOTICE

SZCJ reserves the right to make modifications,enhancements,improvements,corrections or other changes without further notice to any product herein. SZCJ does not assume any liability arising out of the application or use of any product described .