
SZCJ Shenzhen Changji Semiconductor Co., LTD.

DFNWB1.0×0.6-2L Plastic-Encapsulate Diodes

ESDBU18VA1 Bi-direction ESD Protection Diode



DESCRIPTION

Designed to protect voltage sensitive electronic components from ESD and other transients, Excellent clamping capability, low capacitance, and fast response time provide best in class protection on designs that are exposed to ESD.

The combination of small size, low capacitance, and high level of ESD protection makes them a flexible solution for applications such as HDMI, Display Port TM. It is designed to replace multiplayer varistors (MLV) in consumer equipments applications such as mobile phone, notebook, PAD, STB, LCD TV etc.

FEATURES

- Bi-directional ESD protection of one line
- Low capacitance: 0.35pF
- Low reverse clamping voltage
- Reverse stand−off voltage: 18V
- ESD Rating of Class 3(>16Kv) Per Human Body Model
- Excellent package:1.0mm×0.6mm×0.5mm
- Fast response time
- JESD22-A114-B ESD Rating of class 3B per human body model
- IEC 61000-4-2 Level 3 ESD protection

APPLICATIONS

- Computers and peripherals
- High speed data lines
- Audio and video equipment
- Cellular handsets and accessories
- Portable electronics
- USB interfaces
- Other electronics equipments communi-cation systems

MARKING



BH=Device Code

Front Side

MAXIMUM RATINGS (T_a=25℃ unless otherwise noted)

Parameter		Symbol	Limit	Unit
IEC 61000-4-2 ESD Voltage	Air Model	V_{ESD}(1)	±20	kV
	Contact Model		±20	
JESD22-A114-B ESD Voltage	Per Human Body Model		±20	
ESD Voltage	Machine Model		±0.4	
Peak Pulse Power		P_{PP}(2)	48	W
Peak Pulse Current		I_{PP}(2)	4	A
Lead Solder Temperature − Maximum (10 Second Duration)		T_L	260	℃
Storage Temperature Range		T_J,T_{stg}	-55 ~ +150	℃

(1) Device stressed with ten non-repetitive ESD pulses.

(2) Non-repetitive current pulse 8/20μs exponential decay waveform according to IEC61000-4-5.


ESD standards compliance

IEC61000-4-2 Standard


Contact Discharge		Air Discharge	
Level	Test Voltage kV	Level	Test Voltage kV
1	2	1	2
2	4	2	4
3	6	3	8
4	8	4	15

JESD22-A114-B Standard

ESD Class	Human Body Discharge V
0	0～249
1A 1B 1C	250～499 500～999 1000～1999
2	2000～3999
3A 3B	4000～7999 8000～15999




ESD pulse waveform according to IEC61000-4-2



8/20μs pulse waveform according to IEC 61000-4-5

ELECTRICAL PARAMETER

Symbol	Parameter
V_C	Clamping Voltage @ I_{PP}
I_{PP}	Peak Pulse Current
V_{BR}	Breakdown Voltage @ I_T
I_T	Test Current
I_R	Reverse Leakage Current @ V_{RWM}
V_{RWM}	Reverse Standoff Voltage



V-I characteristics for a Bi-directional TVS

ELECTRICAL CHARACTERISTICS(T_a=25℃ unless otherwise specified)


Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Reverse stand off voltage	V_{RWM} (1)				18	V
Reverse leakage current	I_R	V_{RWM}=18V			0.1	μA
Breakdown voltage	$V_{(BR)}$	I_T=1mA	19	21		V
Clamping voltage	V_C (2)	I_{PP}=4A		12		V
Junction capacitance	C_J	V_R=0V,f=1MHz		0.35	0.5	pF

(1) Other voltages available upon request.


(2) Non-repetitive current pulse 8/20μs exponential decay waveform according to IEC61000-4-5

TYPICAL CHARACTERISTICS


TLP Measurement



Capacitance Characteristics




Transmission Line Pulsing (TLP) Measurement




PACKAGE OUTLINE AND PAD LAYOUT INFORMATION

DFNWB1.0× 0.6-2L Package Outline Dimensions



Symbol	Dimensions In Millimeters (mm)		
	Min.	Typ.	Max.
A	0.40	0.45	0.50
A1	0.00	0.03	0.05
D	0.95	1.00	1.08
E	0.55	0.60	0.68
b	0.40	0.50	0.60
e	-	0.65	–
L	0.20	0.25	0.30
L1	0.05 REF.		

DFNWB1.0× 0.6-2L Suggested Pad Layout




Note:
1.Controlling dimension:in millimeters.
2.General tolerance:± 0.050mm.
3.The pad layout is for reference purposes only.

NOTICE
SZCJ reserves the right to make modifications,enhan nts,improvements,corrections or other es without further notice to any product herein. SZCJ does not assume any liability arising out of the application or use of any product described h

TAPE AND REEL INFORMATION

DFN/FBP(1.0×0.6×0.5) Embossed Carrier Tape




Packaging Description:


DFN/FBP(1.0*0.6*0.5) parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 10,000 units per 7" or 17.8cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	a	B	C	d	E	F	P0	P	P1	W
DFN/FBP(1.0×0.6×0.5)	0.66	1.15	0.66	Ø1.50	1.75	3.50	4.00	2.00	2.00	8.00

DFN/FBP(1.0×0.6×0.5) Tape Leader and Trailer



DFN/FBP(1.0×0.6×0.5) Reel



Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
7"Dia	Ø178.00	54.40	13.00	R78.00	R25.60	R6.50	9.50	12.30

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
10000 pcs	7 inch	150,000 pcs	203×203×195	600,000 pcs	438×438×220	