SZCJ


Shenzhen Changji Semiconductor Co., LTD.

JSCJ SOP8 Plastic-Encapsulate MOSFETS

CJQ10SN15S N-Channel Power MOSFET

$V_{(BR)DSS}$	$R_{DS(on)}$TYP	I_D
150 V	40mΩ@10V	10A

SOP8




DESCRIPTION

The CJQ10SN15S uses shielded gate trench technology with a low resistance package to provide extremely low RDS(ON). This device is ideal for load switch and battery protection applications

APPLICATIONS

- Battery protection applications
- Load switch


MARKING



Frontside

Q10SN15S= Device code
Solid dot=Pin1 indicator
Solid dot = Green molding compound device, if none, the normal device
XX=Code

Equivalent Circuit



MAXIMUM RATINGS (T_a=25℃ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	150	V
Gate-Source Voltage	V_{GS}	±20	V
Continuous Drain Current	I_D ①	10	A
Pulsed Drain Current	I_{DM} ②	40	A
Power Dissipation	P_D ⑤	3.0	W
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$ ⑤	41.7	℃/W
Operating Junction and Storage Temperature Range	T_J ,T_{stg}	-55~+150	℃

MOSFET ELECTRICAL CHARACTERISTICS

T_a=25℃ unless otherwise specified

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
Off characteristics							
Drain-source breakdown voltage	$V_{(BR)\ DSS}$	V_{GS} = 0V, I_D =250μA		150			V
Zero gate voltage drain current	I_{DSS}	V_{DS} =120V, V_{GS} =0V	T_J =25℃			1.0	μA
			T_J =125℃			100	
Gate-body leakage current	I_{GSS}	V_{DS} =0V, V_{GS} =±20V				±100	nA
On characteristics ③							
Gate-threshold voltage	$V_{GS(th)}$	V_{DS} =V_{GS}, I_D =250μA		2.0	3.0	4.0	V
Static drain-source on-sate resistance	$R_{DS(on)}$	V_{GS} =10V, I_D =10A			40	52	mΩ
Dynamic characteristics ③④							
Input capacitance	C_{iss}	V_{DS} =25V,V_{GS} =0V, f =1MHz			1150		pF
Output capacitance	C_{oss}				410		
Reverse transfer capacitance	C_{rss}				40		
Gate resistance	R_g	f=1MHz			4.0		Ω
Switching characteristics ③④							
Total gate charge	Q_g	V_{GS}=10V, V_{DS}=80V, I_D=7A			20		nC
Gate-source charge	Q_{gs}				4.7		
Gate-drain charge	Q_{gd}				4.9		
Turn-on delay time	$t_{d(on)}$	V_{DD}=30V,R_L=2.3Ω, V_{GS}=10V, R_G=10Ω			41		ns
Turn-on rise time	t_r				33		
Turn-off delay time	$t_{d(off)}$				93		
Turn-off fall time	t_f				51		
Drain-Source Diode Characteristics							
Drain-source diode forward voltage	V_{SD} ③	V_{GS} =0V, I_S=10A				1.2	V
Continuous drain-source diode forward current	I_S ①					10	A
Pulsed drain-source diode forward current	I_{SM} ②					40	A

Notes:

1.T_C=25℃ Limited only by maximum temperature allowed.

2.P_W≤10μs, Duty cycle≤1%.


3.Pulse Test : Pulse Width≤300μs, duty cycle ≤2%.

4.Guaranteed by design, not subject to production.


5.The value of $R_{\theta JA}$ is measured with the device mounted on 1 in 2 FR-4 board with 2oz. Copper, in a still air environment with T_a=25℃,t≤10sec.

Typical Characteristics


Output Characteristics




Transfer Characteristics




$R_{DS(ON)}$ —— I_D




$R_{DS(ON)}$—— V_{GS}



I_S —— V_{SD}




Threshold Voltage




Typical Characteristics


Capacitances




Gate Charge




NORMALIZED TRAISIENT THERMAL IMPENDANCE




MAXIMUM FORWARD BIASED SAFE OPERATING AREA




SOP8 Package Outline Dimensions





Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	**Max**	**Min**	**Max**
A	1.450	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
b	0.330	0.510	0.013	0.020
c	0.170	0.250	0.007	0.010
D	4.700	5.100	0.185	0.201
e	1.270（BSC）		0.050（BSC）	
E	5.800	6.200	0.228	0.244
E1	3.800	4.000	0.150	0.157
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°

SOP8 Suggested Pad Layout




Note:
1.Controlling dimension:in millimeters.
2.General tolerance:± 0.05mm.
3.The pad layout is for reference purposes only.

NOTICE

SZCJ reserves the right to make modifications,enhan nts,improvements,corrections or other es without further notice to any product herein. SZCJ does not assume any liability arising out of the application or use of any product described h

SOP8 Tape and Reel

SOP8 Embossed Carrier Tape




Packaging Description:

SOP8 parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 4,000 units per 13" or 33cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).


ALL DIM IN mm


Dimensions are in millimeter										
Pkg type	a	B	C	d	E	F	P0	P	P1	W
SOP8	6.40	5.40	2.10	Ø1.50	1.75	5.50	4.00	8.00	2.00	12.00

SOP8 Tape Leader and Trailer



SOP8 Reel





Dimensions are in millimeter								
Reel Option	D	D1	D2	G	H	I	W1	W2
13"Dia	Ø330.00	100.00	13.00	R151.00	R56.00	R6.50	12.40	17.60

REEL	Reel Size	Box	Box Size(mm)	Carton	Carton Size(mm)	G.W.(kg)
4,000 pcs	13 inch	8,000 pcs	360×360×65	40,000 pcs	378×358×382	