
SZCJ

Shenzhen Changji Semiconductor Co., LTD.

PDFNWB5×6-8L Plastic-Encapsulate MOSFETS

CJAC90SN12 N-Channel Power MOSFET

$V_{(BR)DSS}$	$R_{DS(on)}$TYP	I_D
120V	5.7mΩ@10V	90A



DESCRIPTION

The CJAC90SN12 uses shielded gate trench technology and design to provide excellent $R_{DS(ON)}$ with low gate charge. It can be used in a wide variety of applications


FEATURES

- High Power and current handing capability
- Load switch
- High density cell design for ultra low $R_{DS(ON)}$
- Lead free product is acquired
- Good stability and uniformity with high E_{AS}
- Excellent package for good heat dissipation

APPLICATIONS

- SMPS and general purpose applications
- Hard switched and high frequency circuits
- Uninterruptible Power Supply
- Power management

MARKING




CJAC90SN12 = Part No.

Solid dot = Pin1 indicator.

XX = Code.

EQUIVALENT CIRCUIT



MAXIMUM RATINGS (T_a=25℃ unless otherwise noted)

Parameter	Symbol	Limit	Unit
Drain-Source Voltage	V_{DS}	120	V
Gate-Source Voltage	V_{GS}	±20	V
Continuous Drain Current	I_D ①	90	A
Pulsed Drain Current	I_{DM} ②	360	A
Single Pulsed Avalanche Energy	E_{AS} ③	306	mJ
Power Dissipation	P_D ①	235	W
Operating Junction and Storage Temperature Range	T_J ,T_{stg}	-55~+150	℃

Thermal Characteristics

Parameter	Symbol	Value		Unit
		Typ	Max	
Thermal Resistance from Junction to Case	$R_{\theta JC}$ ①	0.35	0.53	℃/W
Thermal Resistance from Junction to Ambient	$R_{\theta JA}$ ⑥	41.6	62.5	℃/W

MOSFET ELECTRICAL CHARACTERISTICS

T_a=25℃ unless otherwise specified

Parameter	Symbol	Test Condition		Min	Typ	Max	Unit
Off characteristics							
Drain-source breakdown voltage	$V_{(BR)DSS}$	V_{GS} = 0V, I_D =250uA		120			V
Zero gate voltage drain current	I_{DSS}	V_{DS} =96V, V_{GS} =0V	T_J =25℃			1	μA
			T_J =125℃			100	
Gate-body leakage current	I_{GSS}	V_{DS} =0V, V_{GS} =±20V				±100	nA
On characteristics ④							
Gate-threshold voltage	$V_{GS(th)}$	V_{DS} =V_{GS}, I_D =250uA		2.0	2.9	4.0	V
Static drain-source on-sate resistance	$R_{DS(on)}$	V_{GS} =10V, I_D =20A			5.7	7	mΩ
Forward transconductance	g_{FS}	V_{DS} =5V, I_D =10A			29		S
Dynamic characteristics ④⑤							
Input capacitance	C_{iss}	V_{DS} =60V,V_{GS} =0V, f =100kHz			3627	7250	pF
Output capacitance	C_{oss}				438	876	
Reverse transfer capacitance	C_{rss}				12	24	
Gate resistance	R_g	f =1MHz			2.5		Ω
Switching characteristics ④⑤							
Total gate charge	Q_g	V_{GS}=10V, V_{DS}=60V, I_D=20A			49	100	nC
Gate-source charge	Q_{gs}				15	30	
Gate-drain charge	Q_{gd}				7	14	
Turn-on delay time	$t_{d(on)}$	V_{DS}=60V,I_D=20A , V_{GS}=10V,R_G=10Ω			16	32	ns
Turn-on rise time	t_r				9	18	
Turn-off delay time	$t_{d(off)}$				27	52	
Turn-off fall time	t_f				12	24	
Drain-Source Diode Characteristics							
Drain-source diode forward voltage	V_{SD} ④	V_{GS} =0V, I_S=10A				1.2	V
Continuous drain-source diode forward current	I_S ①					90	A
Pulsed drain-source diode forward current	I_{SM} ②					360	A
Reverse recovery time	t_{rr}	V_{DD}=60V,I_S=33A, di/dt= 300A/μs		-	36.8	-	ns
Reverse recovery charge	Q_{rr}			-	207.1	-	nC

Notes:

1.T_C=25℃ Limited only by maximum temperature allowed.

2.P_W≤10μs, Duty cycle≤1%.

3.EAS condition: V_{DD}=50V,V_{GS}=10V, L=0.5mH, R_g=25Ω Starting T_J = 25°℃.

4.Pulse Test : Pulse Width≤300μs, duty cycle ≤2%.


5.Guaranteed by design, not subject to production.

6.The value of $R_{\theta JA}$ is measured with the device mounted on 1 in 2 FR-4 board with 2oz. Copper, in a still air environment with T_a=25℃.


szcjsemi.com

Typical Characteristics


Output Characteristics




Transfer Characteristics




$R_{DS(ON)}$ —— I_D




$R_{DS(ON)}$—— V_{GS}



I_S —— V_{SD}




Threshold Voltage




Typical Characteristics


Capacitances




Gate Charge




I_D - T_C




Maximum Safe Operating Area




Transient Thermal Impedance, Junction-Case




PDFNWB5x6-8L Package Outline Dimensions



Top View
[顶视图]




Bottom View
[背视图]



Side View
[侧视图]

Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.000	0.035	0.039
A3	0.254REF.		0.010REF.	
D	4.944	5.096	0.195	0.201
E	5.974	6.126	0.235	0.241
D1	3.910	4.110	0.154	0.162
E1	3.375	3.575	0.133	0.141
D2	4.824	4.976	0.190	0.196
E2	5.674	5.826	0.223	0.229
k	1.190	1.390	0.047	0.055
b	0.350	0.450	0.014	0.018
e	1.270TYP.		0.050TYP.	
L	0.559	0.711	0.022	0.028
L1	0.424	0.576	0.017	0.023
H	0.574	0.726	0.023	0.029
θ	10°	12°	10°	12°

PDFNWB5x6-8L Suggested Pad Layout




Note:
1.Controlling dimension:in millimeters.
2.General tolerance:±0.05mm.
3.The pad layout is for reference purposes only.

NOTICE

JCET reserve the right to make modifications,enhancements, improvements, corrections or other changes without further notice to any product herein.JCET does not assume any liability arising out of the application or use of any product described herein.

PDFNWB5×6-8L Tape and Reel

PDFNWB5×6-8L Embossed Carrier Tape




Packaging Description:


PDFNWB5×6-8L parts are shipped in tape. The carrier tape is made from a dissipative (carbon filled) polycarbonate resin. The cover tape is a multilayer film (Heat Activated Adhesive in nature) primarily composed of polyester film, adhesive layer, sealant, and anti-static sprayed agent. These reeled parts in standard option are shipped with 5,000 units per 13" or 33.0 cm diameter reel. The reels are clear in color and is made of polystyrene plastic (anti-static coated).

Dimensions are in millimeter										
Pkg type	A	B	C	d	E	F	P0	P	P1	W
PDFNWB5×6-8L	6.30	5.30	1.10	Ø1.50	1.75	5.50	4.00	8.00	2.00	12.00

PDFNWB5×6-8L Tape Leader and Trailer



PDFNWB5×6-8L Reel



Dimensions are in millimeter						
Reel Option	**D**	**D1**	**D2**	**G**	**W1**	**W2**
13" Dia	φ330.00	100.00	13.00	1.90	17.60	12.40

Reel	Reel Size	Box	Box Size (mm)	Carton	Carton Size (mm)
5,000 pcs	13 inch	10,000 pcs	360×360×65	50,000 pcs	378×358×382

szcsemi.com